

Trelleborg

Agriculture

Trelleborg tires range



Tractor, combine and sprayer tires

Radial range



TM1000

ProgressiveTraction®



The innovative TM1000 ProgressiveTraction®, designed in compliance with VF regulations, provides superior load capacity, limited soil compaction while providing unbeatable traction. On the road, the new range guarantees low fuel consumption, long life, boosting farming efficiency.

VF 600/70R28 TL PFO NRO*	167D	(164E)
VF 540/65R30 TL PFO NRO	158D	(155E)
VF 600/70R30 TL PFO	170D	(167E)
VF 620/75R30 TL PFO	172D	(169E)
VF 420/85R34 TL PFO	154D	
VF 480/70R34 TL PFO*	158D	
VF 650/60R34 TL PFO	168D	(165E)
VF 710/55R34 TL PFO NRO	170D	(167E)
VF 710/60R34 TL PFO NRO	173D	(170E)
VF 650/65R34 TL PFO	170D	(167E)
VF 650/60R38 TL PFO NRO	170D	(167E)
VF 650/65R38 TL PFO	172D	(169E)
VF 650/85R38 TL PFO	182D	(179E)
VF 710/60R38 TL PFO	174D	(171E)
VF 800/70R38 TL	184D	
VF 800/70R38 TL PFO*	184D	
VF 650/65R42 TL PFO NRO	174D	(171E)
VF 650/75R42 TL PFO	180D	(177E)
VF 650/85R42 TL PFO	183D	(180E)
VF 710/70R42 TL PFO	182D	(179E)
VF 710/75R42 TL PFO	184D	(181E)
VF 900/60R42 TL PFO NRO	189D	(186E)
VF 750/70R44 TL PFO	186D	(183E)
VF 380/85R46 TL PFO	162D	(159E)
VF 750/75R46 TL PFO	189D	(186E)
VF 900/65R46 TL PFO	193D	(190E)
VF 480/80R50 TL PFO*	166D	
VF 480/95R54 TL PFO	180D	(177E)

* = in preparation

TM1000

HIGH POWER



The TM1000 High Power has been designed to equip the latest generation of high powered tractors. It is able to transfer to the ground the entire engine power, along with the torque driven by the latest breed of transmissions.

IF 710/65R46 TL	183D
-----------------	------

TM900

ProgressiveTraction®



The new TM900 ProgressiveTraction® tire is the next step in the evolution of a product that has already made its mark in high-power tractor applications. Ideal for transporting heavy tanks under full load, the tire delivers exceptional reliability in all conditions, easy handling on any terrain and during long road travel. ProgressiveTraction® pattern contributes to increased profitability and performance in farming operations.

600/70R28 TL	157D	(154E)	NEW
600/70R30 TL	158D	(155E)	NEW
710/60R30 TL*	162D	(159E)	
600/70R34 TL*	160D	(157E)	
650/60R34 TL	159D	(156E)	NEW
710/55R34 TL*	164D	(161E)	
710/60R34 TL*	164D	(161E)	
650/75R38 TL*	169D	(166E)	
650/85R38 TL	173D	(170E)	NEW
800/70R38 TL*	178D	(175E)	
900/60R38 TL*	178D	(175E)	
710/70R42 TL	173D	(170E)	NEW
710/75R42 TL	175D	(172E)	NEW
900/60R42 TL*	180D	(177E)	

* = in preparation

TM900

HIGH POWER



Good traction, excellent self-cleaning capability, comfort, low rolling resistance and low fuel consumption make the TM900 High Power the most advanced extra large agricultural radial tire in standard technology.

600/70R28 TL	157D	(154E)
600/70R30 TL	158D	(155E)
710/60R30 TL	162D	(159E)
600/70R34 TL	160D	(157E)
650/60R34 TL	159D	(156E)
710/55R34 TL	164D	(161E)
710/60R34 TL	164D	(161E)
650/75R38 TL	169D	(166E)
650/85R38 TL	173D	(170E)
800/70R38 TL	178D	(175E)
900/60R38 TL	178D	(175E)
710/70R42 TL	173D	(170E)
710/70R42 TL Harvester	173D	(170E)
710/70R42 TL	179A8	*
710/75R42 TL	175D	(172E)
900/60R42 TL	180D	(177E)

* = harvesting application

TM1060



The TM1060 tread design merges the best qualities of Trelleborg's agricultural radial products. Whilst the wing effect maximises the tread width, ensuring an extra wide footprint, the ProgressiveTraction® technology boosts the traction capability. Furthermore, the increased sidewall flexibility leads to very low soil compaction without impacting on the superior tire strength.

VF 480/60R28 TL	145D	
VF 520/60R28 TL NRO	149D	
VF 600/60R28 TL NRO	157D	
VF 600/60R30 TL NRO	158D	
VF 600/60R38 TL NRO	168D	(165E)
VF 650/60R38 TL NRO	166D	
VF 650/60R38 TL NRO	173D	(170E)
VF 710/60R38 TL NRO	171D	
VF 650/60R42 TL PFO NRO	168D	NEW
VF 710/60R42 TL NRO	173D	(170E)
VF 750/70R44 TL	183D	

TM800

PowerFlex



TM800 PowerFlex is designed for high-power tractors working in tough conditions, combining top field performance with excellent road behavior.

Its VF-PFO construction and ProgressiveTraction® tread deliver superior traction, reduced soil compaction, and lower fuel use, while the central rib ensures stability, precision, and comfort during transport.

VF 480/65R28 TL PFO NRO*	148D	(154E)
VF 540/65R28 TL PFO NRO	154D	(151E)
VF 600/65R28 TL PFO NRO*	159D	(156E)
VF 600/65R38 TL PFO NRO*	164D	(161E)
VF 650/65R38 TL PFO NRO	169D	(166E)
VF 710/70R38 TL PFO NRO*	178D	(175E)

* = in preparation

TM800

ProgressiveTraction®



The Trelleborg Tires TM800 ProgressiveTraction® builds on the iconic TM800 line with the integration of the proprietary ProgressiveTraction® technology. This award-winning innovation delivers exceptional traction, driving superior performance across diverse terrains, from soft to hard soils. By optimizing operational efficiency, it reduces working time per hectare, improves fuel economy, and extends tread life, ensuring more productive and cost-effective farming operations. Available also in High Speed technology for selected sizes

440/65R24 TL*	128D	
480/65R24 TL*	140D	
540/65R24 TL*	140D	
540/65R26 TL*	141D	
420/65R28 TL*	135D	(138A8)
440/65R28 TL*	131D	
480/65R28 TL	136D	
540/65R28 TL**	142D	
540/65R28 TL	149D	(146E) High Speed
600/65R28 TL	147D	
600/65R28 TL	154D	(151E) High Speed
540/65R30 TL*	143D	
540/65R34 TL*	145D	
600/65R34 TL*	151D	
540/65R38 TL*	147D	
600/65R38 TL	153D	
650/65R38 TL**	157D	
650/65R38 TL	163D	(159E) High Speed
710/70R38 TL	166D	
710/70R38 TL	171D	(168E) High Speed
600/65R42 TL*	154D	
650/65R42 TL*	158D	

* In preparation

** Available also in Heavy Duty version

TM800



With its outstanding field and road performance, the TM800 has been developed for high power tractors. Excellent traction, superior load capability at high speeds, reduced soil compaction, ride comfort and excellent durability in every working conditions, all enhance the productivity of your farming operations.

320/65R18 TL	109A8	(109B)
340/65R18 TL	113A8	(113B)
440/65R24 TL	128D	
480/65R24 TL	133D	
480/65R24 TL	140D	
540/65R24	140D	
540/65R24 TL*	146A8	
540/65R26 TL	141D	
420/65R28 TL	135D	(138A8)
440/65R28 TL	131D	NEW
480/65R28 TL	136D	
540/65R28 TL**	142D	
600/65R28 TL**	147D	
540/65R30 TL	143D	
540/65R30 TL**	150D	(147E) High Speed
540/65R34 TL	145D	
540/65R34 TL	152D	(149E) High Speed
600/65R34 TL	151D	
600/65R34 TL	157D	(154E) High Speed
540/65R38 TL	147D	
540/65R38 TL	153D	(150E) High Speed
600/65R38 TL	153D	
650/65R38 TL**	157D	
650/65R38 TL	166D	(169A8) High Speed
710/70R38 TL**	166D	
710/70R38 TL	171D	Sugar cane Forage
710/70R38 TL	175D	
600/65R42 TL	154D	
650/65R42 TL	158D	
650/65R42 TL**	165D	(168A8)

* For harvesting applications

** Available also in Heavy Duty version

TM700

ProgressiveTraction®



Leading tractor manufacturers are constantly developing the middle range tractor lines, demanding extra traction performance and fuel efficiency from the tires, with limited space for larger tires. The TM700 ProgressiveTraction® is the answer.

380/70R28 TL	127D	
420/70R28 TL	133D	
480/70R28 TL	140D	
480/70R30 TL	141D	
480/70R34 TL	143A8	(143B)
480/70R34 TL	155A8	(155B)
480/70R38 TL	145D	
520/70R38 TL	150D	
580/70R38 TL	155D	
580/70R42 TL	158D	
620/70R42 TL	166D	

TM700



The TM700 line guarantees outstanding performance. The combination of excellent traction in the field, self-cleaning properties, comfort and driveability on the road, make the first /70 radial tire for agriculture the reference point for high quality tires.

240/70R16 TL	104A8	(104B)
260/70R16 TL	109A8	(109B)
280/70R16 TL	112A8	(112B)
280/70R18 TL	114A8	(114B)
280/70R20 TL	116A8	(116B)
300/70R20 TL	110A8	(110B)
320/70R20 TL	113A8	(113B)
360/70R20 TL	120A8	(120B)
380/70R20 TL	122A8	(122B)
320/70R24 TL	116A8	(116B)
360/70R24 TL	122A8	(122B)
380/70R24 TL	125A8	(125B)
420/70R24 TL	130A8	(130B)
480/70R24 TL	138A8	(138B)
480/70R26 TL	139A8	(139B)
320/70R28 TL	119A8	(119B)
360/70R28 TL	125A8	(125B)
380/70R28 TL	127A8	(127B)
420/70R28 TL	133D	
480/70R28 TL	140D	
480/70R28 TL	145D	(148A8)
420/70R30 TL	134A8	(134B)
480/70R30 TL	141D	
520/70R30 TL	145A8	(145B)
480/70R34 TL	143A8	(143B)
480/70R34 TL	155A8	(155B)
520/70R34 TL	148A8	(148B)
480/70R38 TL	145A8	(145B)
520/70R38 TL	150D	
580/70R38 TL	155D	
580/70R42 TL	158D	
620/70R42 TL	166D	
TM700 HS		
480/70R30	147D	(144E)
520/70R30	151D	(148E)

Tractor, combine and sprayer tires

Radial and Cross-ply range



PneuTrac®



The new PneuTrac® contains the best-in-class features of Trelleborg agricultural tires along with a new sidewall. The innovative "Omega" design of the sidewall helps the tire carcass to sustain load, simultaneously providing flexibility and an extra-wide footprint at very low pressure, resulting in very low soil compaction.

VF 260/70R16 TL	110A8	(110B)
VF 280/70R18 TL	116A8	(116B)
VF 280/70R20 TL	118A8	(118B)
VF 380/70R24 TL	137A8	(137B)
VF 420/70R28 TL	145A8	(145B)
VF 480/65R28 TL	148A8	(148B)

TM200

ProgressiveTraction®



Trelleborg Tires TM200 ProgressiveTraction® is the first product to bring VF (Very High Flexion) technology to specialized crops like vineyards and orchards, where precision, stability, and soil protection are critical. Its low-pressure capability ensures reduced compaction, enhanced traction, and greater comfort. Versatile across conditions, the TM200 ProgressiveTraction® combines an advanced tread design with premium materials to deliver long-lasting performance and optimized fuel efficiency.

VF 280/70R16 TL*	120A8	120B	NEW
VF 320/65R16 TL	128A8	128B	
VF 340/65R18 TL*	130A8	130B	NEW
VF 440/65R24 TL	144A8	144B	
VF 440/65R28 TL*	146A8	146B	

* = in preparation

TM1 ECO POWER



The TM1 ECO POWER is designed also for the new generation of electric tractors. The advanced tire design ensures superior traction on both road and hard soil, enhancing stability, tractor control, maneuverability and operator safety.

280/70R16 TL	112D
340/70R24 TL	124D
380/70R24 TL	130D
480/70R30 TL	147D

TM600



Standard series tire with metric size designed for tubeless fitment.

Key features:

- optimal load capacity and traction
- maximum comfort on the road
- minimum soil compaction, maximum flotation
- excellent self-cleaning

210/95R16 TL	106A8	(106B)	(7.50R16)
210/95R18 TL	108A8	(108B)	(7.50R18)
280/85R20 TL	112A8	(109B)	(11.2R20)
320/85R20 TL	119A8	(116B)	(12.4R20)
250/85R24 TL	112A8	(109B)	
280/85R24 TL	115A8	(112B)	(11.2R24)
320/85R24 TL	122A8	(119B)	(12.4R24)
340/85R24 TL***	125A8	(122B)	(13.6R24)
380/85R24 TL	140A8	(140B)	
380/85R24 TL	131A8	(128B)	(14.9R24)
420/85R24 TL	137A8	(134B)	(16.9R24)
280/85R28 TL	118A8	(115B)	(11.2R28)
320/85R28 TL	124A8	(121B)	(12.4R28)
340/85R28 TL***	127A8	(124B)	(13.6R28)
380/85R28 TL	133A8	(130B)	(14.9R28)
420/85R28 TL***	139A8	(136B)	(16.9R28)
380/85R30 TL*	135A8	(135B)	(14.9R30)
420/85R30 TL***	140A8	(137B)	(16.9R30)
420/90R30 TL	147A8	(147B)	
460/85R30 TL	145A8	(142B)	(18.4R30)
380/85R34 TL	137A8	(137B)	(14.9R34)
380/85R34 TL	142A8	(142B)	(14.9R34)
420/85R34 TL	142A8	(139B)	(16.9R34)
420/85R34 TL***	147A8	(147B)	
460/85R34 TL**	147A8	(144B)	(18.4R34)
340/85R38 TL	132A8	(128B)	
320/85R38 TL	129A8	(126B)	(12.4R38)
340/85R38 TL	133A8	(130B)	(13.6R38)
380/80R38 TL	142A8	(142B)	
380/85R38 TL	144A8	(144B)	(14.9R38)
380/95R38 TL	147A8		
400/75R38 TL	138A8	(135B)	(15.5R38)
420/85R38 TL	144A8	(141B)	(16.9R38)
420/85R38 TL*	149A8	(149B)	(16.9R38)
460/85R38 TL***	149A8	(146B)	(18.4R38)
480/80R38 TL*	149A8	(149B)	
520/85R38 TL***	155A8	(152B)	(20.8R38)
520/85R38 TL*	155A8	(152B)	(20.8R38)
480/80R42 TL***	151A8	(151B)	(18.4R42)
520/85R42 TL***	157A8	(157B)	(20.8R42)
520/85R42 TL	162A8	(162B)	(20.8R42)
480/80R46 TL	158A8	(158B)	(18.4R46)
520/85R46 TL	158A8	(158B)	(20.8R46)
480/80R50 TL	159D		
480/80R50 TL*	159A8	(159B)	RICE
480/95R50 TL*	164A8	(164B)	

* = ProgressiveTraction® version

** = in preparation

*** = available also in Heavy Duty version

TM150



The TM150 is Trelleborg's answer to the new generation of fertilizers and self-propelled high powered sprayers. In line with the VF standards, the new tire can carry high loads while assuring low soil compaction, minimizing ruts and boosting crop yields.

VF 380/90R46 TL CFO	173D	
VF 380/105R46 TL CFO	178D	
VF 480/80R46 TL CFO	177D	
VF 520/85R46 TL CFO	173D	
VF 320/90R50 TL CFO	169D	(166E) NEW
VF 380/105R50 TL CFO	179D	
VF 420/95R50 TL CFO*	179D	(175E)
VF 480/80R50 TL CFO	179D	
VF 520/85R5 TL	177D	
VF 380/105R54 TL	178D	

* = in preparation

TM100



The narrow tire specifically designed for row crop applications.

230/95R32 TL	128A8	(128B)
270/95R32 TL	136A8	(136B)
230/95R36 TL	130A8	(130B)
270/95R38 TL	140A8	(140B)
210/95R44 TL	120A8	(120B)
230/95R44 TL	134A8	(134B)
270/95R44 TL	142A8	(142B)
300/95R46 TL	148A8	(148B)
230/95R48 TL	136A8	(136B)
270/95R48 TL	144A8	(144B)
380/90R50 TL	151A8	(151B)
300/95R52 TL	151A8	(151B)
380/90R54 TL	152A8	(152B)

TM190



Suitable for many different operations and soil types.

Key features:

- top performer in long term usage both on field and on road
- reduced lug height offering very good performance on grassland
- high resistance to impacts

7.50R20 TT	6 PR	
9.5R20 TT	8 PR	
8.3R24 TT	8 PR	
9.5R24 TT	107A8	
12.4R36 TT	124A8	(121B)

Marshland



Specialized line for use on waterlogged and marshy terrain.

The extremely deep lugs, together with the structure of the carcass, provide high traction and flotation.

380/85R38 TL	139A8	(139B)
420/85R38 TL	144A8	(144B)
460/85R38 TL	149A8	(149B)

TM3000



The TM3000 is the Trelleborg's answer to the latest and future generation of harvesters, combines and spreader machines and it is the right choice to boost productivity.

VF 1000/50R25 TL*	184D	
VF 620/70R26 TL CFO	173A8	
VF 750/50R26 TL*	169D	
VF 750/65R26 TL CFO	177A8	(177B)
VF 850/45R26 TL CFO*	172D	(169E) NEW
650/75R32 TL	172A8	
IF 800/65R32 TL CFO°	178A8	
IF 800/65R32 TL CFO**	189A8	
IF 800/70R32 TL CFO°	182A8	
IF 900/65R32 TL CFO*	191A8	(191B)
VF 900/60R32 TL CFO**	193D	(190E)
VF 1050/50R32 TL**°	198D	
VF 1250/50R32 TL CFO**°	207D	(204E) NEW
VF 1050/55R34 TL CFO**	206D	
IF 800/70R38 TL CFO°	187A8	
VF 900/60R38 TL CFO**	196D	
VF 750/60R46 TL CFO*	189D	(186E) NEW

* = spreader

** = in preparation

° = for grain cart application also

TM2000



Radial tire for harvesting machines, result of the most advanced technology of Trelleborg experience in agricultural tires.

620/75R26 TL	166A8	(23.1R26)
650/75R32 TL	172A8	(24.5R32)
710/75R32 TL	177A8	
800/65R32 TL	178A8	(30.5LR32)
900/60R32 TL	181A8	

TM90



The Trelleborg TM90 offers a complete range of sizes for tractors up to 160hp. Engineered as a tubeless tire, the new R-1 tread pattern can be used in a variety of applications, both in the field and on the road.

8-16 TT	6 PR	91A8 CN
8-18 TT	6 PR	94A8
8.3-20 TT	6 PR	96A8 CN
11.2-20 TT	8 PR	111A8
8.3-24 TT/TL	8 PR	105A8
9.5-24 TT/TL	8 PR	112A8
11.2-24 TT/TL	6 PR	110A8
12.4-24 TT/TL	8 PR	121A8
12.4-24 TL	12 PR	124A8 (128A6)
13.6-24 TT/TL	8 PR	123A8
14.9-24 TT/TL	8 PR	128A8
16.9-24 TT	8 PR	133A8
16.9-24 TL	12 PR	136A8 (140A6)
14.9-26 TL	8 PR	129A8
16.9-26 TL Harvester	10 PR	137A6
12.4-28 TT	8 PR	123A8
13.6-28 TT/TL	8 PR	125A8
13.6-28 TL	12 PR	130A8 (134A6)
14.9-28 TT/TL	8 PR	130A8
14.9-28 TL	12 PR	134A8 (138A6)
16.9-28 TL	8 PR	135A8
14.9-30 TL	8 PR	131A8
16.9-30 TT/TL	8 PR	137A8
18.4-30 TT/TL	8 PR	139A8
18.4-30 TL	12 PR	145A8 (149A6)
16.9-34 TT/TL	8 PR	139A8
18.4-34 TT/TL	8 PR	142A8
18.4-34 TL	12 PR	146A8 (151A6)
12.4-36 TT/TL	8 PR	127A8
12.4-36 TL	12 PR	131A8 (135A6)
15.5-38 TT/TL	8 PR	129A8
16.9-38 TT/TL	8 PR	141A8
18.4-38 TT	8 PR	143A8
18.4-38 TL	12 PR	149A8 (153A6)
20.8-38 TL	12 PR	152A8 (156A6)

T414



Twin Tractor. The tire range ideal for tractors and harvesters.

Key features:

- increased output from tractors and pulling machines
- maximum traction
- excellent self-cleaning

400/55-17.5 TL	125A8	(122B)
600/55-26.5 TL	148A8	(145B)
600/55-30.5 TL	150A8	(147B)
600/60-30.5 TL	153A8	(150B)
800/55-30.5 TL	172A8	(168B)
710/65-38 TL	162A8	(158B)
850/50-38 TL	163A8	(160B)
850/60-38 TL	175A8	(172B)
850/55-42 TL	161A8	(157B)

Implement tires

Cross-ply range



T404



T421



T423



T478



Twin Implement. Complete range of low ground pressure tires for machines and implements in the most severe and heavy agricultural service.

- Key features:
- large ground contact area for minimum soil compaction
 - low ground pressure
 - low rolling resistance on soft ground
 - good lateral stability

280/60-15.5	TL	115A8	T421
280/60-15.5	TL	125A8	T421
280/60-15.5	TT	128A8	T478
400/45-15.5	TL	116A8	T423
400/60-15.5	TL	145A8	T404
400/60-15.5	TL	148A8	T404
400/60-15.5	TL	145A8	T478
420/55-17	TL	133A8	T421
420/55-17	TL	145A8	T421
400/55-17.5	TT	131A8	T404
400/55-22.5	TL	147A8	T404
500/45-22.5	TL	146A8	T404

500/60-22.5	TL	155A8	T404
500/60-22.5	TL	155A8	T421
560/45-22.5	TL	154A8	T404
560/60-22.5	TL	167A8	T404
600/50-22.5	TL	156A8	T404
600/50-22.5	TL	156A8	T423
600/50-22.5	TL	165A8	T404
600/50-22.5	TL	168A8	T404
710/40-22.5	TL	158A8	T404
400/60-26.5	TT	147A8	T404
600/55-26.5	TL	166A8	T404
600/55-26.5	TL	166A8	T421

600/55-26.5		173A8	T421
710/45-26.5	TL	169A8	T404
710/45-26.5	TL	169A8	T423 MK2
800/40-26.5	TL	172A8	T404
800/40-26.5	TL	172A8	T423 MK2
650/65-30.5	TL	173A8	T404
710/50-30.5	TL	175A8	T404
710/50-30.5	TL	175A8	T423
750/60-30.5	TL	178A8	T404
800/45-30.5	TL	178A8	T404
800/45-30.5	TL	178A8	T423
850/50-30.5	TL	179A8	T404

T421



T428



T423



T440



Twin Ampt. Agricultural multi purpose and low ground pressure tires for field and road.

- Main applications:
- use at speeds up to 70 km/h as well as in heavy duty applications
 - for machines and implements with high road use

620/50B22.5	TL	160D	T423
650/45B22.5	TL	160D	T440
710/40B22.5	TL	161D	T423
620/55B26.5	TL	166D	T421
650/55B30.5	TL	168D	T428
750/50B30.5	TL	173D	T428
850/45B30.5	TL	176D	T423

T404



Twin Garden Tractor. Low ground pressure tire especially designed for grass and other delicate surfaces.

- Key features:
- maximum flexibility both on hard and soft ground
 - advanced floating properties for minimum compaction and no track formation

400/55-17.5	TL	108A8	T404
400/55-22.5	TL	111A8	T404
600/60-30.5	TL	142A8	T404

Transport equipment

Radial range



HF1000



Twin Radial



The VF and steel belted HF1000 has been designed for big forage wagons and slurry tankers. It delivers excellent flotation and self-cleaning features in the field and a comfortable ride, easy handling and high stability on the road.

VF 800/45R30.5 IMP*	TL	181D
VF 850/50R30.5 IMP*	TL	188D
VF 750/60R30.5 IMP	TL	187D
VF 800/60R32 IMP	TL	191D
VF 800/60R38 IMP*	TL	186D

* = in preparation

Radial implement tire perfect in all working conditions.

- Key features:
- great comfort and even wear
 - excellent self-cleaning
 - reduced fuel consumption
 - excellent ground care

500/60R22.5	TL	155D
560/60R22.5	TL	161D
580/65R22.5	TL	159D
600/50R22.5	TL	159D
600/55R26.5	TL	165D
680/55R26.5	TL	171D
710/50R26.5	TL	170D
650/65R30.5	TL	176D
750/60R30.5	TL	181D
850/50R30.5	TL	182D
800/60R32	TL	185D

Implement Standard and High Speed tires

Cross-ply range



AW305



AF302



T452



AW309 Flotation



T306



Tubeless and load/speed index rated, recommended for trailers.

Key features:

- soft ground contact
- low rolling resistance on road transport
- wide range of sizes

10.0/80-12	TL	8 PR	AW305
10.0/80-12	TL	10 PR	AW305
200/95-12	TL	101A8	AF302
260/90-13	TL	121A8	AF302
260/70-15.3	TL	116A8	AW305
260/70-15.3	TL	126A8	AW305
260/70-15.3	TL	131A8	AW305
300/80-15.3	TL	123A8	T452
300/80-15.3	TL	141A8	T452
300/80-15.3	TL	132A8	AW305
300/80-15.3	TL	141A8	AW305
320/80-15.3	TL	145A8	AW305
180/90-16	TL	100A8	AF302
190/90-16	TL	108A8	AF302
200/90-16	TL	111A8	AF302

210/95-16	TL	120A8	AF302
260/70-16	TL	134A8	AW305
340/55-16	TL	140A8	AW305
340/55-16	TL	140A8	AW309
340/55-16	TL	144A8	AW309
360/65-16	TL	148A8	AW305
360/70-16	TL	137A8	AW305
380/55-17	TL	138A8	AW305
380/55-17	TL	138A8	AW309
420/55-17	TL	143A8	T452
480/45-17	TL	146A8	AW305
480/45-17	TL	150A8	AW309
500/50-17	TL	149A8	AW309
520/50-17	TL	159A8	T306
500/55-20	TL	150A8	AW309

Forestry tires

Cross-ply range



T404



T428



T418 Forestry Skidder



It is specifically designed for log skidding service with maximum penetration and tear resistance. It provides long tire life under the most severe operating conditions. The armored plies protect the carcass against stumps, boulders and rocks.

23.1-26	TL	16 PR
28L-26	TL	20 PR
28L-26	TL	26 PR
24.5-32	TL	16 PR
30.5L-32	TL	20 PR
30.5L-32	TL	26 PR
30.5L-32	TL	32 PR
DH 35.5L-32	TL	24 PR
DH 35.5L-32	TL	30 PR

T414



T440



T421



T480



Twin Forestry. The advanced tire technology applied to develop performance for the forestry range.			
Key features:			
• brilliant stability and comfort			
• reliability			
• best possible pull force and accessibility			
500/45-22.5 TT	129A8	T404	
500/60-22.5 TT	144A8	T421 SB	
600/50-22.5 LS2 TT	149A8	T480 SB	
650/45-22.5 LS2 TT	150A8	T440 SB	
710/40-22.5 LS2 TT	161A8	T480 SB	
710/40-24.5 LS2 TT	163A8	T440 SB	
710/40-24.5 LS2 TT	163A8	T480 SB	
600/55-26.5 LS2 TT	165A8	T440 SB	
600/55-26.5 LS2 TT	165A8	T480 SB	
710/45-26.5 LS2 TT	168A8	T440 SB	
710/45-26.5 LS2 TT	168A8	T480 SB	
710/45-26.5 LS2 TT	173A8	T480 SB	
750/55-26.5 LS2 TT	182A8	T440 SB	
750/55-26.5 LS2 TT	182A8	T480 SB	
800/40-26.5 LS2 TT	170A8	T440 SB	
800/40-26.5 LS2 TT	170A8	T480 SB	
780/50-28.5 LS2 TT	182A8	T480 SB	
600/60-30.5 TT	153A8	T414	
750/45-30.5 LS2 TT	173A8	T428 SB	
600/65-34 LS2 TL	163A8	T440 SB	
710/55-34 LS2 TL	167A8	T440 SB	

T410



Agro Forest. Designed for mixed forestry and agricultural service.		
Key features:		
• high traction		
• good load capability		
• great durability in agricultural operations		
320/85-24	127A8	(124B)
380/85-24	137A8	(134B)
380/85-24 TL	143A8	(140B)
380/85-28	139A8	(136B)
420/85-28	144A8	(141B)
460/85-30	150A8	(147B)
420/85-34	147A8	(144B)
420/85-34 TL	153A8	(150B)
460/85-34	152A8	(149B)
420/85-38	149A8	(146B)
460/85-38	154A8	(151B)
520/85-38	160A8	(157B)

Agro Industrial tires

Radial and cross-ply range



TH400



Radial line designed for telescopic handlers, backhoes and compact loaders. The TH400 represents the perfect solution both for farming and for light industrial applications.

Key features:

- great stability
- excellent safety
- maximum resistance to stress and laceration
- superior traction
- outstanding self-cleaning

11LR16 TL	IND	130A8	
340/80R18 TL	IND	143A8 (143B)	(12.5-18)*
400/70R18 TL	IND	147A8 (147B)	(15.5/70-18)*
400/70R20 TL	IND	149A8 (149B)	(16.0/70-20)*
400/70R24 TL	IND	152A8 (152B)	(16.0/70-24)*
440/80R24 TL	IND	161A8 (161B)	(16.9-24)*
460/70R24 TL	IND	159A8 (159B)	(17.5L-24)*
500/70R24 TL	IND	164A8 (164B)	(19.5L-24)*
480/80R26 TL	IND	160A8 (160B)	(18.4-26)*
440/80R28 TL	IND	156A8 (156B)	(16.9-28)*

* Equivalent size Bias-Imperial

TH500



The Trelleborg TH500 tire perfectly matches the requirements of telehandlers and backhoes operating on hard surfaces. Both on the road and in the yard the TH500 delivers exactly the performance and reliability you need from a tire.

The TH500 tread design is closed in the center to deliver long tire life and on road performance whilst its open shoulder construction ensures excellent self-cleaning clean capabilities.

340/80R18 TL	IND	143A8 (143B)	(12.5-18)*
400/70R18 TL**	IND	147A8 (147B)	(15.5/70-18)*
400/70R20 TL	IND	149A8 (149B)	(16.0/70-20)*
460/70R24 TL	IND	159A8 (159B)	(17.5L-24)*
500/70R24 TL	IND	164A8 (164B)	(19.5L-24)*
480/80R26 TL**	IND	167A8 (167B)	(18.4-26)*

* Equivalent size Bias-Imperial

** in preparation

MPT100



Steel belted tire designed for multi-purpose off-road trucks. The MPT100 stands out for its great wear resistance, stability and comfort while running on or off the road. In the field it delivers excellent traction.

425/75R20	TL	IND	158G	NEW
405/70R20	TL	IND	136G	NEW
445/65R22.5	TL	IND	160G	NEW

Rear tractor industrial tires

Cross-ply range



T459



T440 EXC



T480 EXC



Recommended for excavators, loaders and for machines in urban and industrial operations.

Key features:

- good grip
- braking capability on hard surfaces

600/50-22.5	TL	173A8	T480 EXC
650/45-22.5	TL	175A8	T440 EXC
710/40-22.5	TL	176A8	T480 EXC
620/60B34	TL	175A8	T459 HD
600/65-34	TL	175A8	T440 LD SB

Light service tires

farming, industrial and green areas

Cross-ply range



Wide range of tires from 4" to 15" developed for farming, industrial and green area applications. Also available as complete wheel systems.

DRIVER



T411

GARDENER



T412

HAYRACKER



T413

HIGH GRIP



T415

T49



T421

T63



T430

T94



T446

T310



T448

T462



T463



T501



T510



T513



T521



T522



T523



T528



T530



T533



T536



T537



T539



T550



T559 Turf Grip



T560 ICE



T570



T690



T991



TRACTION



The information and technical data provided in this catalogue are indicative and may be subject to change without prior notice. For up-to-date data and official product specifications, please refer to the product technical sheet available through your sales representative.

Complete wheel range for agricultural and forestry tires



Agricultural Wheels



Trelleborg produces high quality wheels for forestry, agricultural, industrial and earth moving applications with diameters from 3 to 54 inches.

DU0500 mounted on the tractor wheel



The DU0500 is the Trelleborg offer for dual tractor tires.

- Easy to maintain and service
- Easy to mount and demount
- Attached rim and drum for easy handling
- Painted in the original colour of the tractor

THK



Trelleborg High Knurling - THK handles high stress and extreme torque, enabling tractors to work at maximum efficiency and productivity.

Together with Trelleborg Extra Large tires, the THK represents a system that meets all requirements.

The knurling has been increased by 50% compared to the standard version. This, combined with the special black paint, maximises the friction characteristics of the rim when the tire is fitted.



Printed on
recycled paper



Shop our tires online



**Discover our website
and your legal guarantee rights**

Follow us

