

TM2000

Absolute efficiency in harvesting applications



**HIGH LOAD
CAPACITY**



**EXTENDED
TIRE LIFE**



**LATERAL
STABILITY**



**PREMIUM
TRACTION**

Built to perform in harvesting applications, the TM2000 radial tire offers superior traction across all terrains.

Its durable construction handles heavy loads without compromise, while the self-cleaning tread pattern ensures optimal uptime and productivity.



TM2000

- 1 High load capacity assured by a strong casing, and by a large lug width.
- 2 Delivers maximum reliability in the most demanding working conditions, even when carrying high loads, thanks to the robust radial construction, which also guarantees high lateral stability on hilly terrain.
- 3 Excellent self-cleaning thanks to interlug terraces.



Lug footprint comparison - Index

Higher is better



Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rims	Type	Tube
620/75R26 166A8 (23.1R26)	TM2000	633	1590	716	4850	750	DW20B		TUBELESS	
650/75R32 172A8 (24.5R32)	TM2000	662	1817	805	5495	850	DW20B		TUBELESS	24.5-32
710/75R32 177A8	TM2000	735	1850	830	5595	850	DW23B	DW21B	TUBELESS	30.5-32
800/65R32 178A8 (30.5LR32)	TM2000	800	1846	829	5595	875	DW27B	DW25B - DH27 - DW28B	TUBELESS	30.5-32
900/60R32 181A8	TM2000	890	1900	855	5765	900	DW30B	DW27B - DW28B	TUBELESS	30.5-32

The information and technical data provided in this catalogue are indicative and may be subject to change without prior notice. For up-to-date data and official product specifications, please refer to the product technical sheet available through your sales representative.



Follow us



Yokohama TWS S.p.A.
Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy
Phone: +39 0774 3841 - info.tws@yokohama-tws.com
www.trelleborg-tires.com



Shop our tires online



Discover our website
and your legal guarantee rights