



MPX TB Multi Purpose Bias Tire

PREMIUM CONSTRUCTION PNEUMATIC

The Trelleborg MPX TB range is designed for telehandler and compact loader applications in the most demanding environments, providing improved traction, better wear resistance and greater stability on all ground surfaces. The unique lug design delivers excellent self-cleaning and grip on muddy surfaces.

Now available with increased load capacity for heavy duty applications, the MPX TB is also ECE 106 approved to meet European safety regulations.

Main Benefits

- Increased load index for heavy-duty applications
- Improved traction with the new lug shape



Applications




TELEHANDERS




COMPACT WHEEL LOADERS


Tire Features




EXCELLENT WEAR RESISTANCE



ROBUST SIDEWALL



IMPROVED TRACTION



GREATER STABILITY

MPX TB

PREMIUM CONSTRUCTION PNEUMATIC

Size	Tread Pattern	Rim (Permitted)	OD (mm)	SW (mm)	LSD (mm)	RC (mm)	Service Description LI/SS	Tire Load Capacity (Kg) at Speed (Km/h)							Tire Pressure (bar)
								Static	10	10 Cyc.	20	30	40	50	
11L-16 IND	MPX TB TL	W8 x 16 (W8L x 16)	823	286	384	2.489	12 PR 116 A8	2.580	1.400	1.680	1.225	1.165	1.120	1.020	3,60
								2.645	1.440	1.725	1.255	1.200	1.150	1.050	3,85
								2.795	1.520	1.825	1.325	1.265	1.215	1.110	4,15
								2.875	1.565	1.875	1.365	1.300	1.250	1.140	4,40
340/80-18	MPX TB TL	11x18 (W10x18; W11x18; W12x18)	984	330	453	3.090	143 A8	4.085	2.215	2.660	1.930	1.845	1.770	1.610	2,40
								4.640	2.525	3.030	2.200	2.095	2.020	1.835	2,80
								5.205	2.820	3.395	2.465	2.350	2.260	2.060	3,20
								5.590	3.030	3.640	2.645	2.525	2.425	2.200	3,50
								6.270	3.405	4.090	2.970	2.835	2.725	2.500	4,00
400/70-20	MPX TB TL	W13x20 (13x20SDC)	1.059	404	-	3.192	155 A8	6.065	3.295	3.955	2.875	2.740	2.635	2.400	3,20
								6.510	3.535	4.245	3.085	2.940	2.830	2.575	3,50
								7.310	3.975	4.770	3.465	3.305	3.180	2.890	4,00
								8.115	4.410	5.290	3.845	3.665	3.525	3.210	4,50
								8.915	4.845	5.815	4.225	4.030	3.875	3.530	5,00
400/70-24 IND (REPLACES 405/70-24 16/70-24)	MPX TB TL	13 x 24 (13 x 24SDC)	1.174	410	537	3.551	158 A8/158 B	6.645	3.615	4.335	3.150	3.005	2.890	2.890	3,20
								7.135	3.880	4.655	3.385	3.225	3.105	3.105	3,50
								8.015	4.360	5.230	3.800	3.625	3.485	3.485	4,00
								8.895	4.835	5.800	4.220	4.020	3.870	3.870	4,50
								9.775	5.315	6.375	4.635	4.420	4.250	4.250	5,00
400/80-24 IND (15.5/80-24)	MPX TB TL	DW13 x 24 (DW14L x 24) (DW13L x 24)	1.253	410	572	3.825	162 A8	7.430	4.040	4.845	3.520	3.360	3.230	2.940	3,20
								7.975	4.335	5.200	3.780	3.605	3.470	3.155	3,50
								8.960	4.870	5.845	4.250	4.050	3.895	3.545	4,00
								9.940	5.405	6.485	4.715	4.495	4.325	3.935	4,50
								10.925	5.940	7.125	5.180	4.940	4.750	4.325	5,00
400/80-24	MPX TB TL	DW13 (W12; DW12; W13; W14; DW14L)	1.250	404	-	-	162 A8	7.430	4.040	4.845	3.520	3.360	3.230	2.940	3,20
								7.975	4.335	5.200	3.780	3.605	3.470	3.155	3,50
								8.960	4.870	5.845	4.250	4.050	3.895	3.545	4,00
								9.940	5.405	6.485	4.715	4.495	4.325	3.935	4,50
								10.925	5.940	7.125	5.180	4.940	4.750	4.325	5,00
460/70-24 IND (17.5L-24)	MPX TB TL	DW15L x 24 (DW14L x 24) (DW16L x 24)	1.257	455	564	3.813	159 A8	6.540	3.555	4.265	3.100	2.960	2.845	2.585	2,40
								7.450	4.050	4.860	3.530	3.365	3.240	2.945	2,80
								8.355	4.540	5.450	3.960	3.775	3.630	3.305	3,20
								8.960	4.870	5.845	4.245	4.050	3.895	3.540	3,50
								10.065	5.470	6.565	4.770	4.550	4.375	3.980	4,00
500/70-24 IND (19.5L-24)	MPX TB TL	DW16L x 24 (DW15Lx24) (W15Lx24) (W16Lx24)	1.313	502	584	3.936	164 A8	7.475	4.065	4.875	3.545	3.380	3.250	2.960	2,40
								8.510	4.625	5.550	4.035	3.850	3.700	3.365	2,80
								9.545	5.190	6.225	4.525	4.315	4.150	3.775	3,20
								10.235	5.565	6.675	4.850	4.630	4.450	4.050	3,50
								11.500	6.250	7.500	5.450	5.200	5.000	4.550	4,00
480/80-26	MPX TB TL	DW15L (DW16L; DW18L)	1.424	471	636	4.470	167 A8	8.170	4.430	5.320	3.860	3.690	3.540	3.220	2,40
								9.280	5.050	6.060	4.400	4.190	4.040	3.670	2,80
								10.410	5.640	6.790	4.930	4.700	4.520	4.120	3,20
								11.170	6.060	7.280	5.290	5.050	4.850	4.400	3,50
								12.540	6.810	8.180	5.940	5.670	5.450	5.000	4,00
440/80-28	MPX TB TL	DW15L (DW13; DW14L; W15L; W16L; DW16L)	1.410	420	652	4.250	163 A8	7.310	3.960	4.760	3.450	3.300	3.165	2.880	2,40
								8.300	4.515	5.420	3.935	3.745	3.615	3.280	2,80
								9.310	5.045	6.070	4.410	4.205	4.045	3.685	3,20
								9.995	5.420	6.510	4.730	4.515	4.340	3.935	3,50
								11.220	6.090	7.315	5.315	5.070	4.875	4.470	4,00



Follow us



Yokohama TWS S.p.A.
Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy
Phone: +39 0774 3841 – info.tws@yokohama-tws.com
www.trelleborg-tires.com



Shop our tires online



Discover our website