



PREMIUM MATERIALS HANDLING PRESS ON SOLID

ITL

ITL forklift tires are designed for demanding materials handling environments.

Features & Benefits:

- Our premium compounding and bonding process combine to create tires that outlast others in their class.
- The Traction profile offers long wear and distributes the load for excellent stability.
- The Smooth profile provides a greater contact area with the work surface, offering better load distribution and increased stability.
- The larger footprint area creates better traction in most applications for starting and stopping.





TECHNICAL SPECIFICATIONS

Tire Size	Pattern	Load Capacity (lbs)	Weight (lbs)
8½x4x4*	S	1,430	11
9x5x5*	S	1,960	13
10x4x5*	S	1,605	13
10x3x6¼*	S	1,100	9
10x4x6¼*	S	1,600	12
10x5x6¼*	S	2,100	16
10x6x6¼*	S	2,600	19
10x7x6¼*	S	3,100	22
10x4x6½	S	1,585	13
10x4¾x6½	S	1,950	15
10x5x6½	S	2,070	16
10½x5x5	S T	2,250	15
10½x5x6½*	S	2,200	17
10½x6x6½*	S	2,730	20
12x3½x8*	S	1,550	15
12x4x8*	S	1,840	16
12x4½x8*	S	2,140	18
12x5½x8*	S	2,730	23
12x6½x8*	S	3,320	28
13x4½x8*	S	2,350	21
13x5x10	S	2,440	19
13½x4½x8	S	2,350	22
13½x5½x8	S	3,080	28
13½x6½x8*	S	3,810	33
14x4½x8	S	2,390	23
14x5x10	S	2,730	25
15x5x11¼	S	2,850	27
15x6x11¼*	S	3,530	32
15x7x11¼*	S	4,210	39
15x8x11¼*	S	4,890	45
15x9x11¼*	S	5,560	49
15½x5x10*	S T	3,010	30
15½x6x10*	S T	3,820	37
16x5x10½	S T	3,090	32
16x6x10½	S T	3,920	39

Tire Size	Pattern	Load Capacity (lbs)	Weight (lbs)
16x7x10½	S T	4,750	46
16x4x12½/8*	S	2,280	23
16¼x4x11¼*	T	2,310	25
16¼x5x11¼	S T	3,120	32
16¼x6x11¼	S T	3,930	39
16¼x7x11¼	S T	4,740	44
17x4½x12½/8*	T	2,810	29
17x5x12½/8*	S	3,220	26
17x6x12½/8*	S	4,050	40
17x7x12½/8*	S	4,880	52
18x5x12½/8	S	3,360	34
18x6x12½/8	S	4,290	46
18x7x12½/8	S	5,220	48
18x8x12½/8	S	6,150	63
18x9x12½/8*	S	7,080	70
18x5x14*	S	3,300	34
18x6x14	S	4,100	48
18x7x14*	S	4,890	49
18x9x14	G	6,480	69
20x5x16	S	7,430	38
20x6x16	S	3,770	47
20x5x16*	T G	3,570	38
20x6x16*	T G	4,440	47
20x8x16*	T	6,170	63
20x9x16*	T	7,030	71
21x6x15*	T	4,820	57
21x7x15	T	5,870	67
21x8x15	T	6,930	77
21x9x15*	T	7,980	87
21x12x15	T	11,103	118
22x6x16*	T	4,990	59
22x7x16*	T	6,080	69
22x8x16	T	7,170	82
22x9x16	T	8,260	90
22x10x16	T G	9,350	102

Tire Size	Pattern	Load Capacity (lbs)	Weight (lbs)
22x12x16	T G	11,530	129
22x14x16	T	13,710	138
22x16x16	S	15,890	168
22x6x17¾*	S	4,820	53
22x7x17¾	S	5,770	63
22x8x17¾	S	6,725	80
22x10x17¾	S	8,630	91
22x14x17¾	T	12,440	129
26x7x20	T	6,890	87
28x10x22	S G	11,200	140
28x12x22	S T	13,820	175
28x14x22	S G	16,430	210
28x16x22	S G	19,040	245
36x10x30	G	13,530	197
36x12x30	S	16,680	242
36x16x30	S	22,990	300



SPECIAL COMPOUNDS AVAILABLE





Non-Marking Rolling Resistant Abrasion/Cut Resistant

TREAD PATTERNS

Smooth Traction

* Shows MITL on the tire sidewall.



TRELLEBORG

WWW.TRELLEBORG.COM/WHEELS