

T-840

Consistent performance



STABILITY



TRACTION



COOL RUNNING

The daily challenge in material handling is to achieve dependable results without compromising efficiency. The Trelleborg T-840 meets this need with a dense tread design that delivers consistent grip and stability in medium-intensity applications.

Its smart tread design ensures precise steering control, giving operators confidence in everyday operations.

T-840

Built for everyday duty

Bias-ply pneumatic tire designed for medium-intensity applications, delivering reliable results across a wide range of operating conditions.

Ideal for forklifts, loaders, and industrial vehicles working in logistics hubs, warehouses, and manufacturing facilities, the T-840 offers a balanced combination of heat resistance, ride comfort, and durability over time.

This makes it suitable for use at speeds up to 35 km/h, supporting efficient long-distance travel in large material handling environments.

1 Block tread design for improved traction

2 Pattern designed to enhance directional stability

3 Shock-absorbing structure for heavy-duty service



T-840

Size	Alternative Size	Ply Rating	Rim	Tire type & Pattern ● Tube Type ■ Tubeless ▼ Both	Product Dimensions [mm]			Minimal Dual Spacing [mm]	Inflation Pressure [bar]	Load Index	Speed Symbol	Load Capacity [kg]	
					Overall Diameter	Section Width	Tread Depth					Counterbalanced Lift Trucks up to 25 km/h	
												Load Wheel	Steering Wheel
15x4.5-8	125/75-8	12	3.00D-8	●	381	117	8	140	10	100	A5	1.040	800
4.00-8		8 10	3 1/4I-8	●	414	112	6	138	9 10	94 97	A5 A5	870 950	670 730
16x6-8	150/75-8	16	4.33R-8	●	425	152	12	175	10	113	A5	1.495	1.150
18x7-8	180/70-8	14 16	4.33R-8	●	462	173	14	199	9 10	121 125	A5 A5	1.885 2.145	1.450 1.650
5.00-8		8 10	3.00D-8	●	467	132	11	158	8,25 10	106 111	A5 A5	1.235 1.415	950 1.090
21x8-9	200/75-9	14 16	6.00E-9	●	535	200	15	230	9 10	131 134	A5 A5	2.535 2.755	1.950 2.120
6.00-9		10 12	4.00E-9	●	540	160	13	192	8,50 10	118 121	A5 A5	1.715 1.885	1.320 1.450
6.50-10		10 12 14	5.00F-10 (5.50F-10)	●	588	177	14	212 (218)	7,75 9 10	122 125 128	A5 A5 A5	1.950 2.145 2.340	1.500 1.650 1.800
23x10-12	250/60-12	16	8.00G-12	●	594	243	20	293	8	139	A5	3.160	2.430
23x9-10	225/75-10	20	6.50F-10	●	595	225	16	259	10	142	A5	3.340	2.650
7.50-10		12	5.00F-10	●	643	205	15	242	8	133	A5	2.680	2.060
7.00-12		12 14 16	5.00S-12	●	672	192	15	230	8,50 9 10	133 134 136	A5 A5 A5	2.680 2.755 2.910	2.060 2.120 2.240
27x10-12	250/75-12	14 16 20	8.00G-12	●	681	261	18	293	7 8 10	143 146 152	A5 A5 A5	3.545 3.900 4.615	2.725 3.000 3.550
8.15-15	28x9-15	14	7.0-15	●	707	216	18	248	10	146	A5	3.900	3.000
28x12.5-15		20	9.75-15	●	728	274	17	397	9	151	A5	4.535	3.490
250-15	250/70-15	18 20	7.50-15	●	735	250	20	288	9,50 10	153 155	A5 A5	4.745 5.040	3.650 3.875
7.00-15		14	5.50-15 (6.0-15)	●	748	198	17	236 (242)	9,25	140	A5	3.250	2.500
7.50-15		14 16	6.0-15 (6.5-15)	●	772	212	21	254 (260)	9,25 10	144 146	A5 A5	3.640 3.900	2.800 3.000
8.25-15		14 18	6.5-15	●	836	234	23	281	8 10	149 153	A5 A5	4.225 4.745	3.250 3.650
300-15	315/70-15	20 22	8.00-15	●	840	300	23	345	9 10	164 165	A5 A5	6.500 6.695	5.000 5.150

The information and technical data provided in this catalogue are indicative and may be subject to change without prior notice. For up-to-date data and official product specifications, please refer to the product technical sheet available through your sales representative.



Printed on
recycled paper



Shop our tires online



**Discover our website
and your legal guarantee rights**

Follow us

