



PREMIUM MATERIALS HANDLING PNEUMATIC

T-900

Heavy-Duty Performance

The T-900 pneumatic tire was designed for heavy duty use on forklifts and other industrial equipment.

The T-900 has an excellent total value of ownership. Its reinforced sidewall, flat tread and special compounding provide for longer tire life and extra resistance against side impacts. It's the preferred tire of OEMs and a premium choice for today's aggressive applications.

PERFORMANCE DEFINED

TIRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING

Trelleborg is a **leading approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in reduced fuel costs for our customers.

STABILITY

Trelleborg tires are designed with **exceptional stability**. Our tires are engineered to ensure **proper distribution of heat** and to prevent excessive deflection under load.

COMFORT

Trelleborg recognizes the importance of a **safe working environment**. Our products are designed to minimize vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

PREMIUM MATERIALS HANDLING PNEUMATIC

T-900

Tire Size	Alternative Size	Ply Rating	Rim Size	Tire Dimensions (in)		Tread Depth (32nds)	Inflation Pressure (psi)	Tire Type	Load Capacity (lbs)		Weight (lbs)
				Overall Diameter	Section Width				Forklift trucks up to 15 mph		
									Load Wheel	Steering Wheel	
5.00-8		10	3.00D-8	18.4	5.5	16	145	Tube Type	3,120	2,405	16
18x7-8	180/70-8	16	4.33R-8	18.2	6.6	20	145	Tube Type	4,730	3,640	23
6.00-9		12	4.00E-09	21.4	6.3	19	145	Tube Type	4,155	3,195	26
6.50-10		12	5.00F-10	23.2	7.2	21	131	Tube Type	4,730	3,640	31
23x9-10	225/75-10	20	6.50F-10	23.0	9.1	24	145	Tube Type	7,595	5,840	58
7.00-12		14	5.00S-12	26.8	7.5	23	131	Tube Type	6,075	4,675	45
7.00-12		16	5.00S-12	26.8	7.5	23	145	Tube Type	6,415	4,940	45
23x10-12	250/60-12	20	8.00G-12	23.6	9.8	28	145	Tube Type	8,310	6,395	58
27x10-12	250/75-12	16	8.00G-12	27.0	9.8	28	116	Tube Type	8,600	6,615	68
7.00-15	29x8-15	14	5.5-15	29.9	8.0	24	128	Tube Type	7,220	5,555	56
7.50-15		14	6.0-15	30.6	8.5	26	134	Tube Type	8,025	6,175	79
7.50-15		16	6.0-15	30.7	8.3	26	145	Tube Type	8,600	6,615	83
8.25-15		14	6.5-15	33.1	9.7	24	116	Tube Type	9,315	7,165	85
28x9-15	225/75-15 (8.15-15)	14	7.0-15	28.0	9.1	23	145	Tube Type	8,600	6,615	63
250-15	250/70-15	20	7.0-15	29.5	9.4	24	145	Tube Type	11,110	8,545	82
300-15	315/70-15	20	8.0-15	34.8	11.5	29	131	Tube Type	14,330	11,025	114
7.50-16	250/80-16	12	6.00G-16	31.7	8.7	24	116	Tube Type	8,005	6,150	70
9.00-20	270/95-20	14	7.0-20	40.0	10.4	35	131	Tube Type	12,895	9,920	143
10.00-20	290/95-20	16	7.5-20	42.5	11.6	40	131	Tube Type	14,330	11,025	172
11.00-20	300/95-20	18	8.0-20	43.6	12.0	42	145	Tube Type	17,195	13,230	202
12.00-20	330/95-20	20	8.5-20	49.0	12.6	45	145	Tube Type	19,775	15,655	240
12.00-20	330/95-20	24	8.5-20	49.0	12.6	45	151	Tube Type	21,405	16,470	254
12.00-24	330/95-24	20	8.5-24	49.0	12.6	45	145	Tube Type	21,495	16,535	271
12.00-24	330/95-24	24	8.5-24	49.0	12.6	45	151	Tube Type	21,925	16,865	288
14.00-24	385/95-24	24	10.00W-24	53.5	15.0	50	145	Tube Type	27,225	20,945	368
14.00-24	385/95-24	28	10.00W-24	53.5	15.0	50	151	Tube Type	27,780	21,365	429

TREAD PATTERN



T-900



TRELLEBORG.COM/WHEELS