

T-900

Best handling for demanding applications



TIRE LIFE



**PUNCTURE
RESISTANCE**



**COOL
RUNNING**



STABILITY

Designed for demanding applications, the T-900 delivers optimal performance for crucial tasks. Its block tread design and large footprint minimize specific pressure, reduce downtime, and maximize tire life.

The shock-absorbing structure, reinforced sidewalls, and rim guards, protect against impact damage, while the anti-slip bead wire system ensures stability. The T-900 tire provides greater stability for faster load positioning and improved cornering, enhancing efficiency and maintaining a low internal temperature for maximum uptime.

T-900

BIAS PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

Size	Alternative Size	Ply Rating	Rim	Tire type & Pattern	Product Dimensions [mm]			Minimal Dual Spacing [mm]	Inflation Pressure [bar]	Load Index	Speed Symbol	Load Capacity [kg]		
				● Tube Type ■ Tubeless		Overall Diameter	Section Width					Tread Depth	Counterbalanced Lift Trucks up to 25 km/h	
				▼ Both									Load Wheel	Steering Wheel
5.00-8		10	3.00D-8	●	468	140	13	158	10	111	A5	1.415	1.090	
18x7-8	180/70-8	16	4.33R-8	●	462	168	16	199	10	125	A5	2.145	1.650	
6.00-9		12	4.00E-9	●	543	160	15	192	10	121	A5	1.885	1.450	
23x9-10	225/75-10	20	6.50F-10	●	585	230	19	259	10	142	A5	3.445	2.650	
6.50-10		12	5.00F-10	●	590	182	18	212	9	125	A5	2.145	1.650	
23x10-12	250/60-12	20	8.00G-12	●	600	245	22	293	10	145	A5	3.770	2.900	
7.00-12		14	5.00S-12	●	680	191	18	230	9	134	A5	2.755	2.120	
		16							10	136	A5	2.910	2.240	
27x10-12	250/75-12	16	8.00G-12	●	685	250	22	293	8	146	A5	3.900	3.000	
		24							10,4	155	A5	5.040	3.875	
28x9-15	225/75-15 (8.15-15)	14	7.0-15	●	710	230	18	248	10	146	A5	3.900	3.000	
250-15	250/70-15	20	7.0-15	●	742	240	19	282	10	155	A5	5.040	3.875	
7.00-15	29x8-15	14	5.5-15	●	760	204	20	236	8,8	140	A5	3.275	2.520	
7.50-15		16	6.0-15	●	778	215	21	254	10	146	A5	3.900	3.000	
7.50-16	250/80-16	12	6.00G-16	●	805	220	21	254	8	144	A5	3.630	2.790	
300-15	315/70-15	20	8.0-15	●	840	290	23	345	9	164	A5	6.500	5.000	
8.25-15		14	6.5-15	●	841	247	19	281	8	149	A5	4.225	3.250	
		16							9,3	152	A5	4.615	3.550	
355/65-15	32x12½-15 (350-15)	24	9.75-15	●	843	334	29	407	10	170	A5	7.800	6.000	
		32	9.75-15	●	843	334	29	407	12,5	177	A5	9.490	7.300	
		32	9.00-15	■	843	334	29	407	12,5	177	A5	9.490	7.300	
9.00-20	270/95-20	14	7.0-20	●	1.015	265	27	311	9	160	A5	5.850	4.500	
10.00-20	290/95-20	16	7.5-20	●	1.085	294	32	334	9	164	A5	6.500	5.000	
11.00-20	300/95-20	18	8.0-20	●	1.110	302	33	352	10	170	A5	7.800	6.000	
12.00-20	330/95-20	20	8.0-20	●	1.145	325	35	372	10	175	A5	8.970	6.900	
		24							10,4	178	A5	9.710	7.470	
		28							10,9	180	A5	10.400	8.000	
12.00-24	330/95-24	20	8.5-24	●	1.245	320	35	378	10	178	A5	9.750	7.500	
		24							10,4	178	A5	9.945	7.650	
14.00-24	385/95-24	24	10.00W-24	▼	1.360	380	39	450	10	186	A5	12.350	9.500	
		28							10,4	186	A5	12.600	9.690	

The information and technical data provided in this catalogue are indicative and may be subject to change without prior notice. For up-to-date data and official product specifications, please refer to the product technical sheet available through your sales representative.

Subject to technical amendments, printing errors and mistakes in text or illustrations. 09.26



Follow us



Yokohama TWS S.p.A.
Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy
Phone: +39 0774 3841 – info.tws@yokohama-tws.com
www.trelleborg-tires.com



Shop our tires online



Discover our website
and your legal guarantee rights