



Intended for tractors equipped with integral or partial suspensions, characterized by excellent performance both on the road and in the field.

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	17 1,2	23 1,6	26 1,8	29 2,0	32 2,2	35 2,4		
480/70R30 TL	147D (144E)	65 S				2255	2460	2665	2870	3075		
		40 S	1595	1765	2105	2435	2680	2900	3125	3350		
		30 S	1810	2000	2380	2760						



Designed for orchards and vineyards work. Fits medium/low power tractors, on both front and rear wheels.

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
260/70R16 TL	109A8 (109B)	40 S	530	590	700	810	920	1030				
		30 S	570	630	750	870	980	1100	1750 H (#)			
		40 S	580	640	760	880	1000	1120				



Excellent traction, self-cleaning, resistance to wear and a long working life. Low soil compaction. Designed for tubeless mounting.

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
280/85R20 TL (11.2R20)	112A8 (109B)	40 S	745	820	895	970	1045	1120	1905 H (#)			
		30 S	800	880	960	1040	1120	1200				
		40 S	905	1000	1090	1180	1270	1360				

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
380/80R38 TL	142A8 (142B)	40 S	1250	1435	1645	1855	2075	2280	2465	2650	4505 H (#)	
		30 S	1335	1535	1760	1985	2215	2440	2640	2840		
		40 S	1320	1515	1740	1960	2185	2410	2605	2800	4760 H (#)	

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
400/75R38 TL (15.5R38)	138A8 (135B)	40 S	1555	1715	1880	2040	2200	2360	4015 H (#)			
		30 S	1660	1835	2010	2185	2355	2530				
		40 S	1850	2040	2230	2420	2610	2800	4760 H (#)			

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
480/80R46 TL (18.4R46)	158A8 (158B)	40 S	2000	2295	2635	2975	3315	3655	3995	4250	7240 H (#)	
		30 S	2140	2460	2820	3185	3550	3915	4275	4550		


Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
520/85R46 TL (20.8R46)	158A8 (158B)	40 S	2765	3055	3345	3630	3910	4250	7225 H (#)			
		30 S	2960	3270	3580	3885	4185	4550				

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			9 0,6	12 0,8	14 1,0	17 1,2	20 1,4	23 1,6	29 2,0	35 2,4	43 3,0	
480/80R50 TL	159D	40 S	2255	2590	2975	3355	3740	4120	4505	4795	7440 H (#)	
		30 S	2365	2720	3120	3525	3925	4330	4730	5035		



The first Trelleborg Very High Flexion (VF) tyre for sprayer applications. The VF technology allows the tyre to carry a higher load compared to the standard technology, with a lower air pressure. The new TM150 has been specifically designed to ensure high stubble resistance.

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			32 2,2	35 2,4	41 2,8	46 3,2	52 3,6	58 4,0	64 4,4			
VF 380/90R46	173D	Up to 65 km/h (S)	4375	4625	5000	5450	5800	6000	6500			



For the latest and future generations of harvesters and combine machines. It maximizes the load capacity of the tyre at low inflation pressure.


Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	29 2,0	35 2,4	41 2,8	46 3,2		
650/75R32 TL	172A8	40 S	3010	3385	4110	4500	4900	5300	5820	6300		
		30 S	3220	3620	4395	4770	5245	5715	6230	6740		
		10 HT S	3220	3620	4395	4770	5245	5715	6230	6740		

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			17 1,2	20 1,4	23 1,6	26 1,8	29 2,0	32 2,2	35 2,4			
IF 800/65R32 CFO TL	178A8	Up to 40 km/h (*)	5250	5775	6225	6650	6900	7200	7500			
		15 Cyc (*)	8140	8955	9650	10175	10695	11160	11625			
		Up to 40 km/h (*)	5780	6460	7140	7480	7820	8160	8500			

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	29 2,0	35 2,4	41 2,8	46 3,2		
IF 800/70R32 CFO TL	182A8	Up to 40 km/h (*)	5780	6460	7140	7480	7820	8160	8500			
		15 Cyc (*)	8960	10015	11070	11595	12125	12650	13175			
		Up to 40 km/h (*)	6300	7020	7740	8100	8370	8730	9000			

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	29 2,0	35 2,4	41 2,8	46 3,2		
IF 800/70R38 CFO TL	184A8	Up to 40 km/h (*)	9765	10885	12000	12555	12975	13535	13950			

(*) = Single mounting



For combines and harvesting machines, it offers superb loading and traction properties combined with excellent lateral stability and resistance to wear.

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	29 2,0	35 2,4	41 2,8	46 3,2		
620/75R26 TL (23.1R26)	166A8	40 S	2530	2845	3455	3750	4120	4500	4900	5300		
		30 S	2710	3045	3700	4015	4410	4810	5240	5670		
		10 HT S	2710	3045	3700	4015	4410	4810	5240	5670		

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	26 1,8	29 2,0	35 2,4	41 2,8	46 3,2	
650/75R32 TL (24.5R32)	172A8	40 S	3010	3385	4110	4500	4900	5300	5820	6300		
		30 S	3220	3620	4395	4770	5245	5715	6230	6740		
		10 HT S	3220	3620	4395	4770	5245	5715	6230	6740		

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	26 1,8	29 2,0	35 2,4	41 2,8	46 3,2	
710/75R32 TL	177A8	40 S	3490	3925	4760	5170	5680	6195	6750	7300		
		30 S	3735	4195	5095	5530	6080	6625	7220	7815		
		10 HT S	3735	4195	5095	5530	6080	6625	7220	7815		

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	26 1,8	29 2,0	35 2,4	41 2,8	46 3,2	
800/65R32 TL (30.5LR32)	178A8	40 S	3835	4310	5235	5680	6240	6805	7415	8025		
		30 S	3835	4310	5235	5680	6240	6805	7415	8025		
		10 HT S	3795	4290	5280	5680	6240	6805	7415	8025		

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	26 1,8	29 2,0	35 2,4	41 2,8	46 3,2	
900/60R32 TL	181A8	40 S	4065	4595	5650	6270	6975	7505	8210	8830		
		30 S	4065	4595	5650	6270	6975	7505	8210	8830		



Highly practical in the field, it delivers excellent performance on the road. Ideal on all kind of soils.

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	29 2,0	38 3,0	43 3,0	46 3,2	58 4,0	
500/60R22.5 TL	155D	65 S	1380	1555	1900	2060	2340	2830	3120	3250	3550	3875
		40 S	1875	2115	2580	2800	3180	3860	4240	4375	4830	5300
		30 S	2085	2345	2865	3150	3530	4290	4710	4875	5365	5800

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	26 1,8	29 2,0	35 2,4	41 2,8	46 3,2	
560/60R22.5 TL	161D	65 S	1650	1855	2265	2470	2790	3390	3720	3855	4240	4625
		40 S	2240	2520	3080	3360	3795	4610	5060	5240	5765	6290
		30 S	2490	2800	3420	3735	4215	5115	5620	5820	6400	6985

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	26 1,8	29 2,0	35 2,4	41 2,8	46 3,2	
580/65R22.5 TL	159D	65 S	1875	2105	2575	2810	2990	3170	3625	4075	4225	4375
		40 S	2545	2865	3500	3820	4065	4310	4925	5540	5745	5950
		30 S	2825	3180	3885	4240	4515	4785	5470	6155	6380	6610

Size	Load-Index/ Speed Symbol	psi bar	Kmh/h					Kg/Tyre				
			12 0,8	14 1,0	20 1,4	23 1,6	29 2,0	38 3,0	43 3,0	46 3,2		
600/50R22.5 TL	159D	65 S	1575	1750	2145	2320	2625	3195	3500	3635	4025	4375
		40 S	2145	2380								