



HD Smooth

HD Solidflex Smooth

PREMIUM CONSTRUCTION SOLID  
**BRAWLER™ HD  
 LOADER**

Brawler® HD tires are designed to perform in extreme applications such as scrap metal recycling centers, waste transfer stations and mining operations.

These tires feature a two-piece patented wheel and disk system that allows tire and wheel interchangeability by simply changing the disk.

Brawler® HD tires are available aperture free or with elliptical apertures (Solidflex).

**FEATURES AND BENEFITS**

- Up to 3 times more wearable rubber than standard pneumatic tires
- Comfortable ride when compared to foam-filled pneumatic tires
- Steel wheels engineered with the strength and flexibility to handle overloads, excessive torque, severe shear and bending stress
- Custom traction tread available up to 7 inches deep

**APPLICATIONS**

- Waste Transfer Stations
- Metal Recycling
- Construction & Demolition
- Steel Mills & Foundries
- Heavy Industrial
- Quarries & Open Pit Mining
- Underground Mining

PREMIUM CONSTRUCTION SOLID

**BRAWLER™ HD  
LOADER****HD SOLIDFLEX SMOOTH**

Tire Size	Pneumatic Equivalent Size	Overall Diameter (in)	Section Width (in)	Rubber Thickness (in)	Tread Depth (32nds)	Load Capacity 6 mph (lbs)	Weight (lbs)
<b>55x10x18</b>	17.5-25	55.0	18.0	10	160	22,070	1478
<b>59x12x20.5</b>	20.5-25	59.1	20.5	12	208	26,090	1976
<b>62x13x21</b>	20.5-25	62.0	21.0	13	240	27,725	2273
<b>66x16x24</b>	23.5-25	65.9	24.0	16	320	32,330	3043
<b>69x17x28</b>	26.5-25	69.1	28.0	17	352	39,175	3867
<b>73x18x31</b>	29.5-25	73.0	31.0	18	384	44,885	4726
<b>80x18x35</b>	35/65-33	79.9	35.0	18	384	58,535	7055

**HD SMOOTH**

Tire Size	Pneumatic Equivalent Size	Overall Diameter (in)	Section Width (in)	Rubber Thickness (in)	Tread Depth (32nds)	Load Capacity 6 mph (lbs)	Weight (lbs)
<b>55x10x18</b>	17.5-25	55.0	18.0	10	160	29,420	1499
<b>59x12x20.5</b>	20.5-25	59.1	20.5	12	208	34,790	2171
<b>62x13x21</b>	20.5-25	62.0	21.0	13	240	36,960	2396
<b>66x16x24</b>	23.5-25	65.9	24.0	16	320	43,110	3231
<b>69x17x28</b>	26.5-25	69.1	28.0	17	352	52,240	4105
<b>73x18x31</b>	29.5-25	73.0	31.0	18	384	59,855	5010
<b>80x18x35</b>	35/65-33	79.9	35.0	18	384	78,045	7225

**Note: Tread depth on smooth tires indicates wearable rubber.**

Yokohama TWS North America, Inc.  
107 Audubon Road - Building 2 - Suite 205  
Wakefield, MA 01880  
800-948-8473  
info.tws@yokohama-tws.com  
www.trelleborg-tires.com/en-us

Follow us

