



# Twin Forestry. The Pure Quality Solution.



Download the App for free



Tire iBrochure

# Twin Forestry

SIZE	Tread Pattern	LI/SS PR				New Tire		Tire in Service		SLR inch	RC inch	SRI inch	Rim	Tube
		ROAD	PR	FOREST HT	FOREST LT	SW inch	OD inch	SW (max) inch	OD (max) inch					
400/60-15.5 TT	T404 FS		14			15.7	34.4	17.2	35.7		103.1	405	AG13.00	400/60-15.5
500/45-22.5 TT	T404 FS	129A8	12	129A8	136A2	19.7	40.2	20.7	41.1		120.7	485	AG16.00	500/45-22.5
500/60-22.5 TT	T421 SB	144A8	16	144A8	151A2	19.7	46.1	20.7	47.2		138.8	550	AG16.00	500/60-22.5
600/50-22.5 LS2 TT	T428 SB	149A8	16	149A2	156A2	23.6	46.1	24.8	47.2	21.7	138.2	550	AG20.00	600/50-22.5
650/45-22.5 LS2 TT	T422 SB	150A8	16	150A2	157A2	25.6	45.7	26.9	46.8	21.2	137	550	AG20.00	650/45-22.5
710/40-22.5 LS2 TT	T428 SB	151A8	16	151A2	158A2	28	46.1	29.4	46.4	21.3	138.2	550	AG20.00	700/40-22.5
710/40-24.5 LS2 TT	T428 SB	163A8	20	163A2	170A2	28	48	29.3	48.4	22.4	146.3	575	AG24.00	710/40-24.5
600/55-26.5 LS2 TT	T422 SB	165A8	20	165A2	172A2	23.6	52.8	24.8	54.1	24.6	158.3	625	AG20.00	600/55-26.5
600/55-26.5 LS2 TT	T428 SB	165A8	20	165A2	172A2	23.6	52.8	24.8	54.1	24.6	158.3	625	AG20.00	600/55-26.5
710/45-26.5 LS2 TT	T422 SB	163A8	18	163A2	170A2	28	52.8	29.4	53.4	24.6	158.3	625	AG24.00	700/50-26.5
710/45-26.5 LS2 TT	T428 SB	163A8	18	163A2	170A2	28	52.8	29.4	53.4	24.6	158.3	625	AG24.00	700/50-26.5
710/45-26.5 LS2 TT	T422 SB	168A8	20	168A2	175A2	28	52.8	29.4	53.4	24.6	158.3	625	AG24.00	700/50-26.5
710/45-26.5 LS2 TT	T428 SB	168A8	20	168A2	175A2	28	52.8	29.4	53.4	24.6	158.3	625	AG24.00	700/50-26.5
750/50-26.5 LS2 TT	T428 SB	174A8	20	174A2	181A2	29.5	57.7	31	58.1	26.6	173	670	AG24.00	700/50-26.5
710/50-30.5 LS2 TT	T428 SB	173A8	20	173A2	180A2	28	58.5	29.4	59.9	27.6	176.6	700	AG24.00	700/50-30.5
750/45-30.5 LS2 TT	T428 SB	173A8	20	173A2	180A2	29.5	57.7	31	58.9	27.6	173	685	AG24.00	700/50-30.5/ 800/45-30.5
600/60-30.5 LS2 TT	T414 FS	153A8	14	153A2	160A2	23.6	58.9	25.1	60.8		176.6	700	AG20.00	600/60-30.5
600/65-34 LS2 TT	T422 SB	157A8	14	157A2	164A2	23.6	65	24.8	66.6	30.5	194.9	760	DW20A	600/65-34
710/55-34 LS2 TT	T422 SB	161A8	14	161A2	168A2	28	65	29.4	66.6	30.5	194.9	760	DW24A	700/55-34
750/65-34 LS2 TT	T422 SB	169A8	16	169A2	176A2	29.5	72.8	31	74.6	34.4	218.5	850	DW24A	30.5-32



## Twin Forestry 422 The solution for increased accessibility

- Excellent traction without using any anti slide device
- The angle of the lugs gives extra pull force and brilliant accessibility
- The open tread pattern gives the best possible self-cleaning
- The large contact area gives the tire a low ground bearing pressure



## Twin Forestry 428 The solution for all-round service

- The wide, flat tire profile ensures excellent compatibility with tracks and chains
- The extra rubber reinforcement in the shoulder area reduces wear and tear from tracks and chains
- The pattern design allows good traction and self-cleaning
- The large contact area gives the tire a low ground bearing pressure



**TRELLEBORG**

Trelleborg Wheel Systems Americas, Inc  
570 Trelleborg Drive, Spartanburg, SC 29301  
Toll Free Phone Number: 1-866-633-8473  
[www.trelleborg.com/wheels/us](http://www.trelleborg.com/wheels/us)

